

# DS-PDMCK-EG2-WE Wireless Magnet Shock Detector

It is a wireless opening detector that notifies of first signs of room intrusion through a door or window. Combined shock sensor can analysis shocks while ignoring background vibrations

## Key Features

- Magnetic contact combined with shock and tilt detection
- 2 wired inputs extension
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission





## Specification

• Specification	
Detection Performance	
Detection Method	Opening Contact, Shock Sensor
Detection Gap	43mm Max
Sensitivity	Shock Detection: High,Normal,Low
	Tilt Detection: Up to 25°
Feature	
Digital Processing	Support
Tamper Protection	Front,Rear
Environment Temperature	Support
Indicator	Support
Signal Strength Indicator	Support
Interface	
Alarm Input	Normally Closed, Normally Open, Impulse Count
Power Switch	Power Up Enrolling
LED Indicator	Green(MC),Orange(tilt),Red(shock),Blue(alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.6Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	3 years in work status (being triggered 20 times per day)
Power Supply	Battery Powered
Battery Type	CR123A x 1
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	22.5mm × 103mm × 23.2mm
	13mm × 34.4mm × 11.4mm
Weight	60g
Application Scenario	Indoor


## Available Model

DS-PDMCK-EG2-WE



### Accessory

#### Optional



Distributed by

*HIKVISION*°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

**Hikvision Turkey** T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com **Hikvision Russia** T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com